

PREMIUM SERIES

3280

1/2 HP Belt Drive
Garage Door Opener



QUIET, SMOOTH...YET TOUGH AS A STEEL-BELTED TIRE.

For consumers who want both quiet and smooth-running reliability, or simply have rooms positioned above their garage, 3280 is the choice.

1/2 HP heavy-duty motor equipped with Motor Vibration Isolation System (MVIS®)...a revolutionary floating motor design that eliminates powerhead vibration for smooth, quiet performance year after year. One-piece solid-steel T-rail with automatic belt tensioner on trolley. Enhanced belt drive system is engineered for more secure belt grip.

- 200-watt lighting
- Meets all UL325 requirements
- Lifetime motor and belt warranty

ACCESSORIES INCLUDED



Multi-Function Control Panel

The standard in control. Controls garage door and turns opener lights on/off from inside the garage. Locks out radio signals while you're away. Includes adjustable light timer and illuminated oversized push button.



Security+® 3-Button Remote Control

With rolling code technology, you are assured of a new code with every use. Every time you come and go, your code changes to one of over 100-billion new codes, never to be repeated.

At Chamberlain, safety is a major part of our mission. It's our commitment to you and, quite simply, the way we produce products every day. Our LiftMaster® products are designed to move the largest door in your home, safely, securely and by always putting safety first.

LiftMaster®

3280

UNSURPASSED SAFETY AND SECURITY

All LiftMaster® garage door openers are manufactured with the highest level of safety and monitoring systems to ensure safe operation.

- The Protector System® safety sensors reverse the door automatically if the infrared beam is broken, before contact is made.
- Sensing technology will stop the door from closing if contact is made with a person or object.
- Security+® Rolling Code Technology assures a new code is sent every time the remote is used.
- Patented PosiLock® system ensures the door remains securely locked when it is closed.
- Opener light turns on automatically when The Protector System® safety infrared beam is broken.



SECURITY+® 3-BUTTON REMOTE CONTROL (373LM)

- Directional visor clip included
- 5-year 3V lithium battery included
- Features Security+® rolling code technology
- Compatible with LiftMaster® Security+® Garage Door Openers and Radio Controls

MULTI-FUNCTION CONTROL PANEL (78LM)

- Controls garage door and turns opener lights on/off from inside garage
- Includes an adjustable light timer and an illuminated push button for convenience
- Locks out all outside radio signals while you're away



WIRELESS KEYLESS ENTRY WITH SECURITY+® (377LM)

- Open your garage door without using a remote control
- Close with just the push of a button
- Can be programmed with a temporary entry code for friends and service people



SPECIFICATIONS

STANDARD SPECIFICATIONS

DIMENSIONS

Installed Length: 128"
 Maximum Door Opening: 7' 6"*
 Headroom Clearance Required: 2"
 *Up to 10' with optional 8' or 10' rails

CARTONS

Number of Cartons: 2
 Carton 1 Dimensions and Contents:
 20" x 12" x 10"
 Multi-Function Control Panel
 373LM Remote Control
 Garage Door Opener Head
 The Protector System®
 Carton 2 Dimensions and Contents:
 10' 4" x 5" x 5"
 Assembled Solid-Steel T-Rail

SECURITY+® RADIO CONTROLS

Coding System: Smart Receiver
 Code Button and Indicator Light
 Operating Range: 150' (approximately)
 Operating Temperature: -40°F to 150°F
 3-Volt Lithium Battery (Remote Control)
 Frequency: 315MHz
 373LM 3-Button Remote Control
 Security+® Anti-Burglary Coding

CONVENIENCE/SAFETY

The Protector System®
 Emergency/Quick Release
 Automatic Trolley Reconnect
 Ventilation/Pet Opening
 Down Safety Reverse
 Up Safety Stop
 Door Open/Beam Broken/Lights On
 PosiLock®

ELECTRICAL SPECIFICATIONS

POWER

Voltage: 120V AC, 60Hz; Wattage: 540; Current Rating: 4.5
 UL Listings: Yes; Length of Line Cord: 4' (3-prong)

LOGIC TYPE

Solid-State Microcontroller with Built-in Surge Suppressor

LIGHTING

Number of Bulbs: 2
 Maximum Wattage: 100 x 2
 Length of Light Delay: Adjustable
 Type of Light Delay: Solid-State

MECHANICAL SPECIFICATIONS

MOTOR

Horsepower: 1/2
 RPM: 1,625
 Thermal Protection: Automatic
 Lubrication: Permanent

DRIVE MECHANISM

Drive Means: Full Reinforced Drive Belt
 Reduction Means: Gear 16:1
 Door Linkage: Adjustable Door Arm

ADJUSTMENTS

Force: Independent External Up and Down
 Limit: External

TRAVEL RATE

Approximately 7"/Second

SHIPPING WEIGHTS

Head: 28 Lbs.
 Rail: 17 Lbs.

MATERIALS

Chassis: Steel
 Rail: Solid-Steel T
 Trolley: Steel

LIFETIME MOTOR & BELT WARRANTY

1 year on all other parts. For more information, refer to owner's manual. LiftMaster® garage door openers meet all current state and federal regulations and UL safety regulations as of date of manufacture.



The in-vehicle universal remote control. See your automobile dealer for availability.

LiftMaster®

World's #1 Installed Garage Door Opener

THE CHAMBERLAIN GROUP, INC.
 845 Larch Avenue • Elmhurst, IL 60126

www.liftmaster.com



©2011 LM 3280 07/11
 The Chamberlain Group, Inc.
 Printed in U.S.A.

WARNING: Garage doors and openers can be dangerous if not properly installed, tested and operated. Children should be supervised by an adult whenever in or around the garage area.

LMCA3280